

Thanks to its compact size the *argenta® pivotica® Pro* is not only easy to mount in the door, the pivot hinge can also be installed in pivoting floor-to-ceiling-height doors. Because the pivot system is placed inside the door, the *argenta® pivotica® Pro* can be used in both new construction and renovation and it is suitable for floors with underfloor heating.

The door can be opened in both directions and has a holding position at 90°. Due to the active dampers, the door always closes perfectly to zero so it remains in line with the wall. This keeps the sleek design of the wall guaranteed. Finally the *argenta® pivotica® Pro* meets to the EN 1154 standard for door closers.

The *argenta® pivotica® Pro* is also available in a 30 minutes fire rated version with special interdens.

*Finish: brushed stainless steel*

## Advantages

- Invisible
- Active damper with 2 speed control:
- Adjustable bottom plate:
  - Width adjustment: -3 / +3 mm
  - Depth adjustment: -3 / +3 mm
  - Alignment: -4 / +4°
- Suitable for floor-to-ceiling-height doors
- Invisible door closer
- Easy installation
- Free choice of rotating position (hinge point)
- Adjustable outlining (straight outlining)
- Fixed settings at -90° / 0° / 90°
- Child-friendly (easy to open)
- Pivot system to be mounted in the doorpanel and not (as usual) in the floor or ceiling

Maximum door weight	100 kg
Maximum door height	3000 mm
Maximum door width	1000 mm
Door thickness	40 mm

